
Tall Office Pod - 1 Person





Our large single person meeting pod is designed to create a quiet, professional space within open office environments. Ideal for video calls, client conversations, and focused work, it combines acoustic insulation with everyday comfort. An integrated desk supports efficient work sessions, while built-in ventilation, power outlets, and natural LED lighting ensure a seamless experience. Its modular design allows easy placement without permanent construction, making it a flexible solution for modern workplaces.

Tall Office Pod



Silent Space - Decibel Reduction as Its Core

Purpose-built for acoustic performance, ReframeSpace pods deliver superior sound reduction, speech privacy, and a calm interior experience through precisionengineered layered construction.

Sound Pod Design, Simplified

Precision-engineered construction streamlines installation, reduces assembly complexity, and delivers a seamless architectural finish with exceptional consistency.

Designed for Teams

Purpose-built for collaboration, ReframeSpace pods support quick, uninterrupted conversations while maximizing space efficiency through compact, thoughtfully engineered footprints.



Comfort & Privacy in Balance

Whisper-quiet ventilation maintains continuous airflow and all-day comfort within a calm, uninterrupted interior environment.



Tall Office Pod - Technical Specifications



1 Grade-A 30.9dB Sound Reduction

SGS Certified Acoustic Measurement of Speech level reduction. 30.9 dB, ISO 23351-2>2020(E)

2 Optimized Airflow for Comfort

Engineered for optimal airflow—delivering a fresh, comfortable environment without drafts or noise.

Silent Multi Fan efficient airflow without noise

3 Airflow

Dual fan air circulation moving up to 80 cfm x 2 (57s for fullcirculation)

4 External Dimensions

L 1350 × W 1150 × H2330mm
L 53” × W 45” × H 91.7”
Additional Height withCasters: 3.15” / 80 mm (H)

5 Mobility

Wheel Caster for ease of movement. Stationary mode support stand. Seismic Anchors Available upon request. Optional Internal & External Locks or lockless standard door handles

6 Stainless Steel Frame & Tempered Glass

Solid stainless steel provides uncompromising stability. Tempered Glass provides Strength & Clarity.

7 Internal Workspace

L 46.4” × W 42.5” × H 79.9”/
L 1180 × W 1080 × H 2030 mm

8 Electrical

Reliable Lighting – Traditional on/off switch for consistent control.

INPUT: USB-A/USB-C 5V 2.1A(1) 110v outlets, 16A*110v=1760WEthernet Cable Opening

Total 18.4W energy consumption
OUTPUT: AC POWER OUTLET (Plug-n-Play Standard Wall Outlet) 85–265 VAC, 10A, 50–60 Hz

9. 6 Precision-tuned layers

Superior Sound Absorption with a Fully Integrated 6-Layer Panel.

10 Product Weight

827 lbs / 375 kg.

11 Flexible Door Configurations

Dual Door Options – Lockable key or handle-only design included.



Colors



SR10005-1POD-WH/GY



SR10005-1POD-WHT



SR10005-1POD-BL/GY



SR10005-1POD-BLK




SR10005-1POD-WHT/NEW



SR10005-1POD-BLK/NEW

Product Diagram with Measurements



Performance

- Speech level reduction: 30 dB
- Maximum airflow: 63 air changes per hour
- Minimal energy consumption: 53 W

Built for Sustainability,

The one-piece “one-panel-one-side” stainless-steel construction ensures long-lasting durability through multiple installations and reconfigurations without missing parts or complicated fittings.

Integrated mobile casters allow easy movement and quick floor-space reconfiguration.

Built for Efficiency

- Built for the Long Run
The simplified “one-panel-one-side” design enables fast, cost-effective assembly and disassembly.
- Simplified Design and Streamlined Manufacturing
Reduced supply-chain complexity and lower overall production costs deliver exceptional value, combining outstanding durability with high-performance engineering for long-term reliability and performance.



Technical specifications

Soundproofing

- Class-A Soundproofing
- Speech Level Reduction: 30.9 dBDs, A Measured in accordance with ISO23351-1

Ventilation



Maximum Airflow:
63 air changes per hour
80 CFM (134.4 m³/h)

Dimensions

- Exterior Dimensions
- Exterior Size:
L 1350 × W 1150 × H 2330 mm
L 53" × W 45" × H 91.7"
 - Additional Height with Casters:
3.15" / 80 mm (H)
 - Door Size:
206 × 73 cm 1" × 28.7" (H × W)
 - Doorway Opening (Clearance):
203 × 69.9 cm 9" × 27.5" (H × W)
 - Door Swing Clearance:
Extends 7" beyond the existing panel
 - Weight:
827 lb / 375 kg

Internal Dimensions

- Interior Size:
L 1180 × W 1080 × H 2030 mm
L 46.4" × W 42.5" × H 79.9"



Shipping Crate Specifications

Crate Dimensions

Packing Size:
L 89.76" × W 29.53" × H 61.02" / 2280 × 750 × 1550 mm

Shipping Weight

470 kg / 1035 lb



Technical Specifications

Materials

Product Materials

- Soundproof felt
- Proprietary acoustic insulation
- Acoustic plywood
- Soundproof polyester fiberfill
- Exterior stainless-steel panels
- High-quality tempered soundproof glass
- Thickness: 0.315" / 8 mm

Interior Materials

Interior Panels
PET sheets laminated with recycled polyester fabric.

Carpet
Soundproof carpet with anti-static, stain-resistant low-loop pile construction.

Table Material


Density board construction with a durable finished surface.

Seating Materials

Gray nylon upholstery with a fiberglass back frame, high-resilience molded foam cushioning, PU surface finish, and adjustable 4D armrests.

Furniture Dimensions

- Table Dimensions
- Table Size: L 105 x W 50 cm 41.3" x 19.6"
 - "Table Height: 75 cm / 29.5"
 - Maximum Table Load: 50 kg / 110 lb
- Seating Dimensions
- Seat Size: 51 x 51 cm 20" x 20" (W x D)
 - Seat Height: Adjustable from 46–56 cm 18"–22"
 - Maximum Seat Load: 200 kg / 440 lb



Safety

Fire Safety

An optional pre-drilled opening for a pendant fire sprinkler head can be utilized during installation or added later.

Support for a standalone fire-suppression system is available upon request.

Seismic Safety

An optional seismic anchoring kit is available.

It includes reinforced brackets designed to enhance the pod's structural stability during strong seismic events.




Technical Specifications

Power and Space Requirements

Power

- Outlets
- 2 × power outlets with USB-A and USB-C ports
- Power Consumption
- 6500K / 36 W dimmable LED light ×1
 - 0.7 A / 8.4 W silent dual-fan ventilation system ×2
- Input Power
- 110–240 VAC, 10A, 50–60 Hz
- AC Output (Power Outlet)
- 110–240 VAC, 10A, 50–60 Hz
- USB-A / USB-C Output
- DC 5V / 2.1A
 - Dual-port simultaneous charging: 1A
 - PD fast charging supported



Space Requirements


- Door Swing Angle 180°

Door Handedness

- Right-handed by default

Dimensions and Clearance Requirements

- Pod Depth (Back to Front, Including Doorway): 189 cm / 74.4"
- Minimum Room Height: 240 cm / 94.5"
- Seismic Anchoring: Allow 50 cm / 19.7" of free space outside each exterior panel wall.
- Independent Fire-Suppression System: Provide 25.4 cm / 10" of clearance above the pod ceiling.
- Sprinkler Installation: Please consult your local fire department for region-specific clearance requirements.



Installation Space

Installation requires an additional 24" of free space around the pod during assembly and installation.

Mobility

All models come pre-installed with casters, allowing easy relocation without disassembly.

To move the pod, raise the support stands until the casters contact the floor, then lower the stands once the pod is in position.

